



PRODUCT SHOWCASE

Innovative techniques, systems and equipment designed to save time and money...




Master Bond Inc.

Quartz Filled, Heat Resistant Epoxy

Master Bond Supreme 45HTQ is a two component, quartz filled epoxy for high performance structural bonding, casting and sealing. This epoxy produces high strength bonds while maintaining exceptional resistance to

thermal cycling and many harsh chemicals.

www.masterbond.com



Inline Services

Pit Cleaning Pig®

Inline Services' Pit Cleaning Pig® is built for heavy duty cleaning. The steel body is encompassed by steel wire pencil brushes and polyurethane discs that scrape along the pipeline and make for an aggressive circumferential cleaning. This mandrel bodied pig is very efficient for rust, black powder and mill

scale removal. To find out more visit us at www.inlineservices.com or call 888-973-0079.

www.inlineservices.com



Universal Vortex

Universal Vortex offers non-freeze pressure regulation/reduction technology to reduce pressure without gas preheat. Our products are applicable to the natural gas transmission, power generation, CNG industries. No moving parts, no carbon emissions, no fuel loss, no freeze ups. 100% reliability, over 2,000+ installations worldwide.

www.universal-vortex.com



Reef Industries

Protect pipelines from unwanted dig-ins by installing Terra Tape® underground warning tape. Terra Tape® is an extrusion laminated identification system available in detectable and non-detectable grades. All Terra Tape® underground marking tapes can be custom printed in up to four colors. 1800.231.6074

www.terratape.com



Denso Protal 7200

Denso's Protal 7200 is a 100% solids, fast cure epoxy coating that can be hand or spray applied to girth welds, tie-ins, fittings and rehabilitation of existing pipelines. Exhibits outstanding abrasion and chemical resistance and has excellent cathodic disbondment results. For information on all your corrosion protection needs, contact Denso at 1-281-821-3355.

www.densona.com



Midwestern Manufacturing

M583CH sideboom attachment on the CAT D8R LGP provides operators with greater visibility and new, enhanced controls for optimal performance. The M583CH features a high capacity winch package with two-speed piston motors, and a low compact, hydraulically operated counter weight system for a lift capacity of 140,000 lb.

981-858-4234

www.sidebooms.com



AMERICAN PETROLEUM INSTITUTE
Individual Certification Programs: ICP™



BECOME AN API CERTIFIED PIPELINE CONSTRUCTION INSPECTOR AND GET BUSY.

The oil and natural gas industry needs qualified API inspectors. Sign up for the next available exam and prove your knowledge. Find your calling.

www.api.org/pipelineinspector



Vermeer

Vermeer D100x140 S3

The Vermeer D100x140 S3 Navigator® horizontal directional drill has a Tier 4 final engine and provides 100,000 pounds (450 kN) of thrust/pull-back and 14,000 ft-lb (19,000 Nm) of rotational torque, plus increased rotational speed of 203 rpm, providing the power downhole to improve productivity.



EZ Line


Supports the Oil & Gas Industry

Contact E-Z Line today for your Adjustable Pipe Supports, Pipe Clamps & Pipe Guides — 2" thru 60" Pipe Size, Shim Blocks - Steel or Epoxy, Pipe Shoes.

Structural Steel Fabricators of: Platforms, Structures, Pipe Racks, Embeds — ¼" thru 1½" Stud Gun Capacity, Skids, Plate Rolling and Pipe

Bending. E-Z Line utilizes 3-D Modeling Software to prepare shop and custom design drawings of platforms and structures. Schedules field trips to prepare custom design drawings to meet your requirements.

www.ezline.com



ProSoft Technology

Have an outdoor SCADA system or wide-ranging application that you need wireless communications for? Our Frequency Hopping radios offer up to 30 miles of point-to-point connectivity at 1.1 Mbps. They feature Smart Switch technology, which allows you to determine which radio's data needs to transmit at a given time, optimizing your Ethernet bandwidth. The Ethernet radios are available for 900 MHz or 2.4 GHz frequencies, and feature 128-bit AES encryption.

<http://psft.com/BAK>