

MIDWESTERN

TRIPLE "LINE SAGGING" WINCH ATTACHMENT

M60TL5W

shown on a
JD 950J Dozer
(Rear screen not shown)



WINCH CONTROLS

The Hydraulic Pilot Controls allow precise, simultaneous control of the winches and include built-in 2-speed function switches.

Controls also include toggle switches with safety guards for the free spool functions.

FEATURES AND SPECIFICATIONS

- Attachment pins directly to the dozer's rear pin-up mount
- System interconnects to the dozer's existing hydraulic system
- 3/4" X 300 ft (6 x 37 EIPS, IWRC) wire rope installed on each winch
- Total attachment weight = 8,100 lbs

WINCH PERFORMANCE

(Based on 2,225 psi and 37 gpm each with 3/4" wire rope)

| LAYER | LOW SPEED / HIGH SPEED | | DRUM CAPACITY (FT) |
|-------|------------------------|------------------|--------------------|
| | LINE PULL (LBS) | LINE SPEED (FPM) | |
| 1 | 49,290/24,960 | 21/42 | 62 |
| 2 | 44,370/22,190 | 23/47 | 132 |
| 3 | 39,930/19,970 | 26/52 | 210 |
| 4 | 36,300/18,150 | 29/58 | 295 |
| 5 | 33,280/16,640 | 31/63 | 388 |

