



## M50-TLSW

on JD850L WLT



Inquire with our sales team for specific models and configurations tailored to meet your needs.



## TRIPLE LINE SAGGING WINCH ATTACHMENT



### INTEGRATED CONTROLS AND CAMERA

## FEATURES

**Precise Controls** allow for simultaneous control of all three winches with electro-hydraulic controls.

**Enhanced Functionality** with all new Paddle and Switch Control Panel with LED indicators for user friendly ergonomics and operations.

**Direct Mount** design for easy bolt on attachment to the rear implement mount plate.

**Heavy Duty Wire Rope** 300 ft of 3/4" 6 x 37 EIPS IWRC wire rope installed on each winch.

**Durable Construction** to meet the most demanding applications with steel housing and total attachment weight of 8,500 lbs.

**Camera System** included to view wire rope spooling and work connections.

## WINCH PERFORMANCE

LAYER	LOW SPEED / HIGH SPEED		DRUM CAPACITY (FT)
	LINE PULL (LBS)	LINE SPEED (FPM)	
1	40,428/20,214	20/39	69
2	35,936/17,968	22/44	147
3	32,343/16,171	25/49	233
4	29,402/14,701	27/54	328

(Based on 1,750 psi and 34.5 gpm each with 3/4" wire rope)